

# 2-1/2" Chrome Plated Brass (Chrome Case)



- Gauge type typically used non-corrosive gas applications
- Dual scale dial face, PSI / kPa
- Clean for oxygen service

## Specifications:

**Pressure Range:** -30" Hg to 6,000 PSI

**Size:** 2-1/2" nominal diameter

**Temperature Range:** -40° C to 60° C

**Inlet Stems:** 1/4" NPT (M)

**Accuracy:** 3%

## Materials:

**Bourdon Tube:** Beryllium Copper

**Inlet Stem:** Chrome Plated Brass

**Case:** Chrome Plated Steel

**Lens:** Polycarbonate

## ORDERING INFORMATION

Part No	Pressure Range	Major Graduations		Minor Graduations		Special Comments
		PSI	kPa	PSI	kPa	
G0213	0 – 30 PSI (200kPa)	5	25	1	5	
G0214	0 – 30 PSI (200kPa)	5	50	1	5	Marked for acetylene use
G8056	0 – 60 PSI (400kPa)	10	100	2	10	
G8058	0 – 200 PSI (1,400kPa)	20	200	5	50	
G8059	0 – 400 PSI (2,800kPa)	50	400	10	100	
G8060	0 – 600 PSI (4,200 kPa)	100	500	20	100	
G8205	0 – 1,000 PSI (7,000kPa)	100	1,000	20	200	
G0516	0 – 4,000 PSI (28,000kPa)	500	4,000	100	1,000	
G8206	0 – 6,000 PSI (42,000kPa)	1,000	10,000	200	1,000	
G8207	0 – 10,000 PSI (70,000 kPa)	1,000	10,000	200	2,000	