

2" Brass (Brushed Brass Case)



- Gauge type typically used non-corrosive gases applications
- Dual scale dial face, PSI / kPa
- Vacuum scale range on lower pressure range versions
- Clean for oxygen service
- Optional Bar / PSI dual scale models available

Specifications:

Pressure Range: -30" Hg to 6,000 PSI

Size: 2" nominal diameter

Temperature Range: -40° C to 60° C

Inlet Stems: ¼" NPT (M)

Accuracy: 3%

Materials:

Bourdon Tube: Beryllium Copper

Inlet Stem: Brass

Case: Brushed Brass

Lens: Polycarbonate

ORDERING INFORMATION

Part No	Pressure Range	Major Graduations		Minor Graduations		Special Comments
		PSI	kPa	PSI	kPa	
G8301	-30"Hg – 30 PSI (200kPa)	5	25	1	5	
G8302	-30"Hg – 100 PSI (700kPa)	10	100	2	20	
G8302	-30"Hg – 200 PSI (1,400kPa)	20	200	5	50	
G8303	0 – 300 PSI (2,100kPa)	50	250	10	50	
G8304	0 – 400 PSI (2,800kPa)	50	400	10	100	
G8305	0 – 1,000 PSI (7,000kPa)	100	1,000	20	200	
G8306	0 – 4,000 PSI (28,000kPa)	500	4,000	100	1,000	
G8307	0 – 6,000 PSI (42,000kPa)	1,000	5,000	200	1,000	