

## 2" Chrome Plated Brass (Chrome Case)



- Gauge type typically used on non-corrosive gas applications
- Dual scale dial face, PSI / kPa
- Vacuum scale range on lower pressure range versions
- Clean for oxygen service

### Specifications:

**Pressure Range:** -30" Hg to 6,000 PSI

**Size:** 2" nominal diameter

**Temperature Range:** -40° C to 60° C

**Inlet Stems:** 1/4" NPT (M)

**Accuracy:** 3%

### Materials:

**Bourdon Tube:** Beryllium Copper

**Inlet Stem:** Chrome Plated Brass

**Case:** Chrome Plated Steel

**Lens:** Polycarbonate

### ORDERING INFORMATION

| Part No | Pressure Range               | Major Graduations |       | Minor Graduations |       | Special Comments |
|---------|------------------------------|-------------------|-------|-------------------|-------|------------------|
|         |                              | PSI               | kPa   | PSI               | kPa   |                  |
| G10079  | - 30"Hg – 30 PSI (200kPa)    | 5                 | 25    | 1                 | 5     |                  |
| G0578   | - 30"Hg – 100 PSI (700kPa)   | 10                | 100   | 2                 | 20    |                  |
| G10027  | - 30"Hg – 200 PSI (1,400kPa) | 20                | 200   | 5                 | 50    |                  |
| G8314   | 0 – 300 PSI (2,100kPa)       | 50                | 250   | 10                | 50    |                  |
| G10026  | 0 – 400 PSI (2,800kPa)       | 50                | 400   | 10                | 100   |                  |
| G8315   | 0 – 1,000 PSI (7,000kPa)     | 100               | 1,000 | 20                | 200   |                  |
| G10025  | 0 – 4,000 PSI (28,000kPa)    | 500               | 4,000 | 100               | 1,000 |                  |
| G8316   | 0 – 6,000 PSI (42,000kPa)    | 1,000             | 5,000 | 200               | 1,000 |                  |