

# 202 Series

# Single Stage Brass Bodied Scientific Regulator



- Pressure ranges of 0-15 to 0-200 PSI are available to cater for a broad range of applications
- Forged body design
- Large diaphragm design
- High flow capacity
- Capsule seat design for greater serviceability and life
- 316L stainless steel diaphragm

The 202 Series regulators are intended for primary pressure control of non-corrosive, high purity or liquefied gases, or where minor fluctuations in outlet pressure (as gas supply diminishes) can be tolerated.

### Specifications:

**Max. Inlet Pressure:** 3000 PSI (210 BAR)

**Gauges:** 2-1/2" diameter brass (chrome plated)

**Temperature Range:** -40° C to 60° C

**Body Ports:** 1/4" FPT

**Helium Leak Integrity:** 1 x 10<sup>-8</sup> scc/sec

**Cv:** 0.2

**Weight:** 1.8 kg

### Materials:

**Body:** Chrome plated forged brass

**Bonnet:** Chrome plated diecast zinc

**Seat:** PTFE

**Filter:** 10 micron sintered bronze

**Diaphragm:** 316L stainless steel

**Internal Seals:** PTFE

### ORDERING INFORMATION

S202 - XXX - XXX - XXX - XX

Series	Outlet Pressure	Inlet Fitting	Outlet Fitting	Options
202	15 (0-15 psi)	T10 (AS2473 Type 10)	4F (1/4" NPT Female)	Inlet Purge
	15 (0-15 psi) acetylene	T20 (AS2473 Type 20)	2S (1/8" Tube)	
	40 (0-40 psi)	T30 (AS2473 Type 30)	4S (1/4" Tube)	
	120 (0-120 psi)	T50 (AS2473 Type 50)	8S (1/2" Tube)	
	200 (0-200 psi)	T60 (AS2473 Type 60)	2B (1/8" Hose Barb)	
		350 (CGA350)	4B (1/4" Hose Barb)	
		540 (CGA540)	FA (Fine adjust valve)	
		580 (CGA580)	4M (1/4" NPT Male)	
		4F (1/4" NPT Female)	DK (1/4" Diaphragm valve)	
		Others by description	Others by description	