

2" Stainless Steel (Chrome Case)



- Gauge type typically used on corrosive gases in non-corrosive environments
- Dual scale dial face, PSI / kPa
- Vacuum scale range on lower pressure range versions
- Clean for oxygen service

Specifications:

Pressure Range: -30" Hg to 4000 PSI

Size: 2" nominal diameter

Temperature Range: -40° C to 60° C

Inlet Stems: ¼" NPT (M)

Accuracy: 3%

Materials:

Bourdon Tube: 316L Stainless Steel

Inlet Stem: 316L Stainless Steel

Case: Chrome plated steel

Lens: Polycarbonate

ORDERING INFORMATION

Part No	Pressure Range	Major Graduations		Minor Graduations		Special Comments
		PSI	kPa	PSI	kPa	
G0210	-30"Hg – 30 PSI (200kPa)	5	25	1	5	
G0211	-30"Hg – 60 PSI (400kPa)	10	100	1	10	
G0212	-30"Hg – 100 PSI (700kPa)	10	100	2	20	
G10030	-30"Hg – 200 PSI (1,400kPa)	20	200	5	50	
G10029	0 – 400 PSI (2,800kPa)	50	400	10	100	
G8148	0 – 600 PSI (4,200kPa)	100	500	20	100	
G10028	0 – 4,000 PSI (28,000kPa)	500	4,000	100	1,000	